

Section1:IDENTIFICATION

1.1 PRODUCTIDENTIFIER

ProductName:

Basalite Cement Mixes 47# and 94# (Portland Cements, Type II, Type V, Block, Plastic, White)

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Use:

Various.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address:

Basalite Concrete Products 605 Industrial Way Dixon, CA 95620

TelephoneNumber:

707-678-1901

1.4 EMERGENCYTELEPHONENUMBER

Emergency Telephone Number:	CHEMTREC 800-424-9300 INTERNATIONAL + 01-703-527-3887	
Dateof Preparation:	February 1, 2013 Version #: 1.1	

Section2:HAZARD(S)IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL

Hazard class

Acute toxicity 4 (Oral) Skin irritation 2 Serious eye damage 1 Skin sensitization 1 Carcinogenicity 1A Specific target organ toxicity - Single exposure 3 Specific target organ toxicity - Repeated exposure 1

2.2 LABELELEMENTS



understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust.

	If swallowed: Immediately call a poison center/doctor. Rinse mouth. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
Storage:	Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal:	Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 ADDITIONAL INFORMATION

Hazardsnototherwise		
classified:	Not applicable.	

60.0% of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

Section3:COMPOSITION/INFORMATIONONINGREDIENTS

3.1MIXTURES

Ingredient	UN #	H / F/ R / *	CASNo	Wt. %
Portland cement	Notavailable.	1/0/0	65997-15-1	60 - 100
Ferric oxide	UN1376	1/0/0	1309-37-1	10 - 30
Silica, crystalline, quartz	Notavailable.	Notavailable.	14808-60-7	3 - 7
Calcium oxide	UN1910	3/0/1	1305-78-8	3 - 7
Gypsum	UN3077	Notavailable.	13397-24-5	3 - 7
Calcium carbonate	Notavailable.	1/0/0	1317-65-3	3 - 7
Magnesium oxide	UN1418	2/0/0	1309-48-4	3 - 7

The exact percentage (concentration) of chemicals has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

*Per NOM-018-STPS-2000

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

Skin:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
Inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
Ingestion:	If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.
4.2 MOSTIMPORTANTSYM	PTOMS AND EFFECTS, BOTH ACUTE AND DELAYED
Eye:	Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Skin:	Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.
Inhalation:	May cause respiratory tract irritation.
Ingestion:	Harmful if swallowed. May cause stomach distress, nausea or vomiting.
4.3 INDICATIONOFANYIMM	EDIATEMEDICALATTENTIONANDSPECIALTREATMENTSNEEDED
Note to Physicians:	Symptoms may not appear immediately.
SpecificTreatments:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).
	Section5:FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

SuitableExtinguishingMedia:	Treat for surrounding material.
Unsuitable Extinguishing Media:	Not available.
5.2 SPECIAL HAZARDS ARISING FROM	THE CHEMICAL
ProductsofCombustion: May in	clude, and are not limited to: oxides of carbon.
5.3 SPECIAL PROTECTIVE EQUIPMENT	AND PRECAUTIONS FOR FIRE FIGHTERS
Keep upwind of fire. Wear full fire fightir	ng turn-out gear (full Bunker gear) and respiratory protection

(SCBA).

Section 6: ACCIDENTALRELEASEMEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENTANDE MERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING-UP

Protective Equipment (PPE). Vacuum or sweep material and place in a disposal container.
Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling:	Avoid contact with skin and eyes. Do not swallow. Good housekeeping is important to prevent accumulation of dust. Avoid generating and breathing dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking. (See section 8)
GeneralHygieneAdvice:	Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.
7.2 CONDITIONS FOR SAFE STOP	AGE, INCLUDING ANY INCOMPATIBILITIES
Storage:	Keep out of the reach of children. Store in dust-tight, dry, labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. (See section 10)

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

ExposureGuidelines

OccupationalExposureLimits				
Ingredient OSHA-PEL ACGIH-TLV				
Portland cement Ferric oxide	15 mg/m³ (total); 5 mg/m³ (resp) 10 mg/m³	1 mg/m³ (no asbestos and <1% crystalline silica, respirable fraction) 5 mg/m³ (iron oxide fume; dust as Fe)		
Silica, crystalline, quartz Calcium oxide	((10 mg/m ³)/(%SiO ₂ +2) TWA (resp)) ((30 mg/m ³)/(%SiO ₂ +2) TWA (total)) ((250)/(%SiO ₂ +5) mppcf TWA (resp)) 5 mg/m ³	0.025 mg/m ³ 2 mg/m ³		
Gypsum	15 mg/m ³ TWA (poussière totale) 5 mg/m ³ TWA (fraction respirable)	10 mg/m ³		
Calcium carbonate Magnesium oxide	15 mg/m³ (total); 5 mg/m³ (resp) 15 mg/m³	10 mg/m ³ 10 mg/m ³		

8.2 EXPOSURE CONTROLS

EngineeringControls:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUALPROTECTIVEMEASSURES

PersonalProtectiveEquipment:

Eye/FaceProtection:	Wear approved eye (properly fitted dust- or splash-proof chemical sa goggles) / face (face shield) protection.	
Skin Protection:		
Hand Protec	tion:	Wear suitable waterproof gloves.
BodyProtecti	on:	Wear suitable waterproof protective clothing.
Respiratory Protection:	poorl exce direc requi	DSH approved dust mask or filtering facepiece is recommended in y ventilated areas or when permissible exposure limits may be eded. Respirators should be selected by and used under the tion of a trained health and safety professional following rements found in OSHA's respirator standard (29 CFR 1910.134) ANSI's standard for respiratory protection (Z88.2).

General Health and Safety	Handle according to established industrial hygiene and safety
Measures:	practices. Do not eat, smoke or drink where material is handled,
	processed or stored. Wash hands carefully before eating or smoking.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Powder.
Color:	Not available.
Odor:	Not available.
Odor Threshold:	Not available.
PhysicalState:	Powder.
pH:	12 - 13
MeltingPoint/FreezingPoint:	Not available.
Initial Boiling Point and Boiling Range:	Not available.
FlashPoint:	Not available.
Evaporation Rate:	Not available.
Flammability:	Not Flammable.
Lower Flammability/Explosive Limit:	Not available.
Upper Flammability/Explosive Limit:	Not available.
VaporPressure:	Not available.
VaporDensity:	Not available.
Relative Density/Specific Gravity:	Not available.
Solubility:	Not available.
Partition coefficient: n-octanol/water: N	ot available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.

Viscosity:

Percent Volatile, wt. %:

VOC content, wt. %:

Not available.

Not available.

0%, Not applicable; 0 wt, Not applicable.

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICALSTABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3 POSSIBILITYOFHAZARDOUSREACTIONS

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

Incompatible materials. Moisture.

10.5 INCOMPATIBLE MATERIALS

None known.

10.6 HAZARDOUSDECOMPOSITIONPRODUCTS

May include, and are not limited to: oxides of carbon.

Section11:TOXICOLOGICALINFORMATION

11.1 INFORMATIONONTOXICOLOGICALEFFECTS

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicologicalcharacteristics:

- **Eye:** Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Skin: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.

Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

AcuteToxicity:

Ingredient	IDLH	LC50	LD50
Portland cement Ferric oxide	5000 mg/m ³ 2500 mg Fe/m ³	Not available. Not available.	Not available. Oral >10000 mg/kg, rat
Silica, crystalline, quartz Calcium oxide	Ca [25 mg/m ³ (cristobalite, tridymite) 50 ma/m ³ (auartz, triboli)1 25 mg/m ³	Not available. Not available.	Oral 500 mg/kg,rat Oral 500 mg/kg, rat
Gypsum	Not available.	Not available.	Not available.

Calcium carbonate Magnesium oxide		ot available. 750 mg/m ³	Notava Notava		Not available. Oral >5000 mg/kg, rat
	Calculate	d overall Chemical Acut	teToxicity	Values	
LC50 (inhalat		LD50(oral)	<u></u>		LD50(dermal)
Not availab		1603.8 mg/kg, ra	+		Not available.
Not availab	ie.	1005.011g/kg,1a	l		Not available:
Ingredient			Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*		
Portland cement					G-A4
Ferric oxide				G-A4, I-3	
Silica, crystalline, qu	artz			G-A2, I-1, N-1, CP65	
Calcium oxide					Not listed.
Gypsum					Not listed.
Calcium carbonate				1	Not listed.
Magnesium oxide					G-A4
11.2 DELAYED, IMM	EDIATE, AND	CHRONICEFFECTSOF	SHORT-AI	ND LONG	-TERMEXPOSURE
Skin Corrosion/Irrita	ation:	Causes skin irritation moisture.	. May cau	se burns i	n the presence of
SeriousEyeDamage/Irritation:		Causes serious eye damage. May cause burns in the presence of moisture.			
Respiratory Sensitiz	zation:	Based on available data, the classification criteria are not met.			
Skin Sensitization:		May cause an allergic skin reaction.			
STOT-Single Exposure:		May cause respirator	May cause respiratory irritation.		
ChronicHealth Effects: Respirable crystalline silica in the form of quartz or cristob from occupational sources is listed by the International Age for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure respirable crystalline silica has been known to cause silico lung disease, which may be disabling. While there may be factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and th severity of the disease is clearly related to the amount of of exposure and the length of time (usually years) of exposure		e International Agency ional Toxicology olonged exposure to wn to cause silicosis, a /hile there may be a n exposure to ing silicosis and the o the amount of dust			
Car	Carcinogenicity: May cause cancer.				
Germ Cell Mutagenicity:		This product is not classified as a mutagen.			
ReproductiveToxic	ity:				
Developmental:		Based on available data, the classification criteria are not met.			
	Fertility:	Based on available d	ata, the cla	assificatio	n criteria are not met.
STOT-Repeated Exp	posure:	Causes damage to organs through prolonged or repeation exposure.		nged or repeated	
Aspiration Hazard:		Based on available d	ata, the cla	assificatio	n criteria are not met.
ToxicologicallySy Materials:	nergistic	Not available.			

Other Information:

Not available.

Section12: ECOLOGICALINFORMATION

12.1 ECOTOXICITY - ENVIRONMENTAL EFFECT ON AQUATIC HABITAT:

Uncured cementitious materials or finely divided (crushed) concrete material is an environmental hazard, which may adversely affect fish and other wildlife. Do not use crushed concrete as fill near any aquatic habitat. Dispose of construction debris containing cement, including empty bags at a permitted landfill or by a disposal firm. Discharge of large quantities to any waterways would be expected to cause significant consequence on aquatic habitat. Do not use crushed concrete as fill near any aquatic habitat.

12.2 PERSISTENCE AND DEGRADABILITY

Not available.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation:

Not available.

12.4 MOBILITY IN SOIL

Not available.

12.5 OTHERADVERSEEFFECTS Not available.

Section13:DISPOSALCONSIDERATIONS

13.1 WASTETREATMENTMETHODS

Disposal Method: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. Otherdisposalrecommendations: Not available. Section14: TRANSPORTINFORMATION 14.1 UN NUMBER TDG DOT NOM-004-SCT2-1994 Not regulated. Not regulated. Not regulated. 14.2 UNPROPERSHIPPING NAME DOT TDG NOM-004-SCT2-1994 Not applicable. Not applicable. Not applicable. 14.3 TRANSPORTHAZARDCLASS(ES) DOT TDG NOM-004-SCT2-1994 Not applicable. Not applicable. Not applicable. **14.4 PACKING GROUP** DOT TDG NOM-004-SCT2-1994 Not applicable. Not applicable. Not applicable. **14.5 ENVIRONMENTAL HAZARDS** Not available. 14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE Not available. Trade Name: Basalite Cement Mixes Page 8 of 10

14.7 SPECIALPRECAUTIONSFORUSER

Do not handle until all safety precautions have been read and understood.

Section15:REGULATORYINFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR291910.1200) HazCom 2012

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

SARA Title III				
Ingredient	Section302 (EHS)TPQ(lbs.)	Section304 EHS RQ (lbs.)	CERCLA RQ(lbs.)	Section313
Portland cement	Not listed.	Not listed.	Not listed.	Not listed.
Ferric oxide	Not listed.	Not listed.	Not listed.	Not listed.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Calcium oxide	Not listed.	Not listed.	Not listed.	Not listed.
Gypsum	Not listed.	Not listed.	Not listed.	Not listed.
Calcium carbonate	Not listed.	Not listed.	Not listed.	Not listed.
Magnesium oxide	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

CaliforniaProposition 65 Warning:

This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient	USA TSCA
Portland cement	Yes.
Ferric oxide	Yes.
Silica, crystalline, quartz	Yes.
Calcium oxide	Yes.
Gypsum	No.
Calcium carbonate	Yes.
Magnesium oxide	Yes.

NFPA-National Fire Protection Association:		
Health:	3	
Fire:	1	
Reactivity:	0	

HMIS - Hazardous Materials Identification System		
Health:	3*	
Fire:	1	
Reactivity:	0	

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

Mexico Classification:



Blue = Health	Red = Flammability Yellow = Reactivity White = Special			
Hazard Rating	Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme			
SOURCE AG	ENCY CARCINOGEN CLASSIFICATIONS:			
CP65	California Proposition65			
OSHA(O)	Occupational Safetyand Health Administration.			
ACGIH (G)	 American Conference of Governmental IndustrialHygienists. A1 - Confirmed human carcinogen. A2 - Suspected human carcinogen. A3 - Animal carcinogen. A4 - Not classifiable as a human carcinogen. A5 - Not suspected as a human carcinogen. 			
IARC (I)	 International Agency for Research on Cancer. 1 - The agent (mixture) is carcinogenic to humans. 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals. 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals. 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans. 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans. 			
NTP (N)	NTP (N)NationalToxicologyProgram.1 - Known to be carcinogens.2 - Reasonably anticipated to be carcinogens.			
Section 16: OTHERINFORMATION				
Dateof Preparation: February 1, 2013				

	1 obraary 1, 2010
Version:	1.1
RevisionDate:	April 23, 2015 - Basalite address updated

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Preparedby:	NexregComplianceInc.
	Phone: (519) 488-5126
	www.nexreg.com

End of Safety Data Sheet